

FREQUENCY STABILITY

OVER:

OPERATING TEMP. RANGE: See note 1

OVERALL STABILITY: $< \pm 50\text{ppm}^*$

INCLUDING:

- OVER OPERATING TEMPERATURE RANGE
- ADJUSTMENT @ 25°C
- LONG TERM AGING (1 YEAR)
- STABILITY OVER SUPPLY VOLTAGE $\pm 10\%$
- STABILITY OVER LOAD (MIN. TO MAX.)

POWER SUPPLY

SUPPLY VOLTAGE: $V_{dd} = 5V \pm 10\%^*$

INPUT CURRENT: $< 15\text{mA}^*$

OUTPUT

OUTPUT SIGNAL: HC-MOS compatible *

SYMMETRY: 40 / 60% (min.) @ $V_{dd} / 2^*$

RISE & FALL TIME: $t_r < 7\text{ns}$ $t_f < 7\text{ns}^*$

LEVEL "0" & "1": $< 0.4V$ $> V_{dd} - 0.5V$

START-UP TIME: $< 5\text{ms}$

FAN OUT (LOAD): 10 TTL / LS *

ENVIRONMENT

OPERABLE TEMP. RANGE: -55 to $+125^\circ\text{C}$

STORAGE TEMP. RANGE: -65 to $+125^\circ\text{C}$

VIBRATIONS: 10 to 2000Hz / 10g

SHOCKS: 5000g, 0.3ms, $\frac{1}{2}$ sine

PACKAGE: Ceramic

PACKAGE DIMENSIONS: 8.0 x 3.7 x 2.0mm

(see packaging info)

PROCESSING: Reflow soldering 260°C / 10s max.
(see packaging info)

MISCELLANEOUS

* Customer's specification on request

Note 1: Operating Temperature Range

MCSO1-A: 0 to $+70^\circ\text{C}$

MCSO1-B: -40 to $+85^\circ\text{C}$

MCSO1-C: -55 to $+125^\circ\text{C}$

Option 1: Enable / Disable (on request)

See application circuit on page 2 for details

Pin 1:	Pin 3 (Fout):
Open	Clock
H	Clock
L	High Z
Not available for $f < 500\text{kHz}$	

Marking Example

Micro Crystal		Micro Crystal	
MCSO1T-B	E/D	Type	Option 1
20.000 MHz	09.44	Frequency	Date Code
O		O (PIN 1)	

Ordering Information Example

MCSO1	T	B	20MHz	E/D	xxx
Oscillator Type	T = Tight Tolerance		Oscillator Output Frequency	Option 1: E/D = Enable / Disable	Customer spec N°
MCSO1 = Miniature Surface Mount Clock Crystal Oscillator A = 0 to $+70^\circ\text{C}$ B = -40 to $+85^\circ\text{C}$ C = -55 to $+125^\circ\text{C}$ X = Custom spec.					

STANDARD FREQUENCIES [MHz]

10.0000	10.1500	10.2300	10.2400	11.0592	12.0000
12.2880	12.8000	13.0000	14.7456	16.0000	16.3840
18.4320	19.2000	19.6608	20.0000	& sub multiple	

Date :	May 2009	Revision No. : 1	Revision Date : 05-09
--------	----------	------------------	-----------------------

Page 1 / 2

In accordance with our policy of continuous development and improvement,
we reserve the right to modify the design or the specifications of our products without prior notice.

Headquarters:	Micro Crystal AG	Tel.	+41 32 655 82 82
	Mühlestrasse 14	Fax	+41 32 655 80 90
	CH-2540 Grenchen	Internet	www.microcrystal.ch
	Switzerland	Email	sales@microcrystal.ch